



# Registration Information Carbon Footprint of Products (CFP)



1. Product information			
1.1	Registration number	CR-DG01-160012	1.7 Product photo 
1.2	Product name	ApeosPort-V C7776	
1.3	Model name / number	ApeosPort-V C7776	
1.4	Main specifications of product	Print speed (Color/Mono): 70ppm Paper size: SRA3(320x450mm) maximum Capable of duplex printing, facsimile and scanning Product Size: 640(W)x699(D)x1143(H) (mm) Product weight: 146kg	
1.5	CFP quantification unit	Per unit product	
1.6	CFP release date	2016/3/7	

2. Company Information		
2.1	Company name (in English)	Fuji Xerox Co., Ltd.
2.2	Phone number (incl. area code)	+81-3-6271-5111

3. CFP quantification results, and description of CFP declaration																					
3.1	CFP quantification results	4,500	kg-CO <sub>2</sub> e																		
Breakdown (by life cycle stage, by process, by flow, etc.)																					
3.2	Raw material acquisition stage	810	kg-CO <sub>2</sub> e																		
	Production stage	72	kg-CO <sub>2</sub> e																		
	Distribution stage	21	kg-CO <sub>2</sub> e																		
	Use & maintenance stage	3,400	kg-CO <sub>2</sub> e																		
	Disposal & recycling stage	130	kg-CO <sub>2</sub> e																		
Value and description of additional info.																					
	Value to be stated on the mark	<Numerical value>	<Value on CFP mark>																		
		<b>4,500kg</b>	per unit product																		
3.3	Description of additional info.	<p>*Calculated by the standard Scenario for MFP (EP type) *CO<sub>2</sub> emission in the distribution stage assumes Taiwan as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in Taiwan. *The CO<sub>2</sub> emission due to printing paper is excluded from the use and maintenance stage. *Print volume is assumed 2,940,000 sheets.</p>  <table border="1" style="margin-left: 20px;"> <caption>CFP Breakdown by Life Cycle Stage</caption> <thead> <tr> <th>Life Cycle Stage</th> <th>CO<sub>2</sub> Emission (kg-CO<sub>2</sub>e)</th> <th>Percentage</th> </tr> </thead> <tbody> <tr> <td>Raw material acquisition stage</td> <td>810</td> <td>18%</td> </tr> <tr> <td>Production stage</td> <td>72</td> <td>-</td> </tr> <tr> <td>Distribution stage</td> <td>21</td> <td>-</td> </tr> <tr> <td>Use &amp; maintenance stage</td> <td>3,400</td> <td>77%</td> </tr> <tr> <td>Disposal &amp; recycling stage</td> <td>130</td> <td>-</td> </tr> </tbody> </table>		Life Cycle Stage	CO <sub>2</sub> Emission (kg-CO <sub>2</sub> e)	Percentage	Raw material acquisition stage	810	18%	Production stage	72	-	Distribution stage	21	-	Use & maintenance stage	3,400	77%	Disposal & recycling stage	130	-
Life Cycle Stage	CO <sub>2</sub> Emission (kg-CO <sub>2</sub> e)	Percentage																			
Raw material acquisition stage	810	18%																			
Production stage	72	-																			
Distribution stage	21	-																			
Use & maintenance stage	3,400	77%																			
Disposal & recycling stage	130	-																			
3.4	Remarks	<p>*Print volume: 2,940,000 sheets *In this scenario, the CO<sub>2</sub> emissions from copy papers are estimated 23,000 kg-CO<sub>2</sub>e at 4.0 g per A4 paper.</p>																			

4. Interpretation of CFP quantification results		
4.1	Interpretation of CFP quantification results	<p>CO<sub>2</sub> emission in use and maintenance stage is the largest as 77%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user.</p> <p>A choice of the use condition (print mode, print conditions and so on) can reduce the CO<sub>2</sub> emission during product usage. For example, 860kg-CO<sub>2</sub>e of the CO<sub>2</sub> emissions (approximately 19%) can be reduced if 2-in-1 print is applied to 1,470,000sheets (50% of print volume).</p> <p>Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.</p>

5. Conditions of quantification					
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
5.3	Assumptions of secondary data used	Basic secondary data v.1.01 is preferentially used. Available secondary data (country v.1.04、foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.			

6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	—
6.3	Verification ID	CV-DG01-160012	6.4	Valid period of verification	2016/2/26

7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	<a href="http://www.cfp-japan.jp/">http://www.cfp-japan.jp/</a>
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	—
---	---------	---

For secondary data, please refer to the information on the following CFP website.  
<http://www.cfp-japan.jp/calculate/verify/data.html>