Registration Information
Carbon Footprint of Products (CFP)

1. Product information			
1.1	Registration number	CR-DG01-15028	1.7 Product photo
1.2	Product name	Dell Color Cloud Multifunction Printer H825cdw	
1.3	Model name / number	Dell Color Cloud Multifunction Printer H825cdw	
1.4	Main specifications of product	Print speed (Letter): 30ppm color/black-and-white Paper size: A4 maximum Capable of duplex printing, facsimile, scanning, NFC and Wifi Product Size: 429(W)x503.5(D)x500(H) (mm) Product weight: 29.2kg	
1.5	CFP quantification unit	Per unit product	
1.6	CFP release date	2015/10/29	

2. Company Information		
2.1	Company name (in English)	Fuji Xerox Co., Ltd.
2.2	Phone number (incl. area code)	+81-3-6271-5111

3. CFP quantification results, and description of CFP declration			
3.1	CFP quantification results	1,300	kg-CO_2e
3.2	Breakdown (by life cycle stage, by process, by flow, etc.)		
	Raw material acquisition stage	180	kg-CO_2e
	Production stage	25	kg-CO_2e
	Distribution stage	21	kg-CO_2e
	Use & maintenance stage	1,000	kg-CO_2e
	Disposal & recycling stage	47	kg-CO_2e
3.3	Value and description of additional info.		
	Value to be stated on the mark	<Numerial value>: **1,300kg**	<Value on CFP mark>: per unit product
	Description of additional info.	*Calculated by the standard Scenario for Printer (EP type) *CO_2 emission in the distribution stage assumes North America as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption -rate in North America. *The CO_2 emission due to printing paper is excluded from the use and maintenance stage. *Print volume is assumed 540,000 sheets.	
3.4	Remarks	*Print volume: 540,000 sheets *In this scenario, the CO_2 emissions from copy papers are estimated 4,200 kg-CO_2e at 4.0 g per A4 paper.	

4. Interpretation of CFP quantification results		
4.1	Interpretation of CFP quantification results	CO_2 emission in use and maintenance stage is the largest as 78%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO_2 emission during product usage. For example, 255kg-CO_2e of the CO_2 emissions (approximately 20%) can be reduced if 2-in-1 print is applied to 270,000sheets (50% of print volume). Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.

5. Conditions of quantification					
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
5.3	Assumptions of secondary data used	Basic secondary data v.1.01 is preferertially used. Available secondary data (country v.1.04、foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.			

6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	–
6.3	Verification ID	CV-DG01-15028	6.4	Valid period of verification	2015/10/13

7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	―

For secondary data, please refer to the information on the following CFP website.
http://www.cfp-japan.jp/calculate/verify/data.html