



Registration information of Carbon Footprint of Products

1. Product information			
1.1	Registration number	CR-DG01-15014-A	1.7 Product photo 
1.2	Product name	Xerox WorkCentre 5335 Multifunction Printer STD	
1.3	Product model	Xerox WorkCentre 5335 Multifunction Printer STD	
1.4	Main specifications of product	Print speed: 35ppm black-and-white Paper size: A3 maximum Capable of duplex printing, facsimile and scanning Product Size: 597(W)x637.5(D)x1115(H) (mm) Product weight: 85kg	
1.5	CFP quantification unit	Per unit product	
1.6	Date of release	2015/3/24	

2. Company Information		
2.1	Company name	FUJIFILM Business Innovation Corp.
2.2	Phone number	+81-3-6271-5111

3. CFP quantification results, and contents of CFP declaration			
3.1	CFP quantification results	1,700	kg-CO ₂ e (CFP quantification results can be slightly different from sum of the following breakdown for rounding of fractions.)
Breakdown (by life cycle stage, by process, by flow, etc.)			
3.2	Raw material acquisition stage	620	kg-CO ₂ e
	Production stage	34	kg-CO ₂ e
	Distribution stage	50	kg-CO ₂ e
	Use & maintenance stage	850	kg-CO ₂ e
	Disposal & recycling stage	99	kg-CO ₂ e
Value in a mark, and contents of additional info.			
3.3	Value in a mark	<Contents>	<Unit for the value in a mark>
		1,700 kg	per unit product
3.3	Contents of additional info.	<p>*Calculated by the standard Scenario for Multifunction Printer (EP type) *CO₂ emission in the distribution stage assumes North America as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in North America. *The CO₂ emission due to printing paper is excluded from the use and maintenance stage. *Print volume is assumed 735,000 sheets.</p> <div style="display: flex; align-items: center;">  <div style="margin-left: 20px;"> <p>51%</p> <p>38%</p> <ul style="list-style-type: none"> ■ Raw material acquisition stage ■ Production stage ■ Distribution stage ■ Use & maintenance stage ■ Disposal & recycling stage </div> </div>	
3.4	Remarks		

4. Interpretation of CFP quantification results		
4.1	Interpretation of CFP quantification results	<p>CO₂ emission in use and maintenance stage is the largest as 51%. It is important to save energy during product usage.</p> <p>The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO₂ emission during product usage.</p> <p>CO₂ emission in raw material acquisition stage is the second largest as 38%. It is also important to reduce size and weight.</p> <p>Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.</p>

5. Conditions of quantification					
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
5.3	Assumptions of secondary data used	Basic secondary data v.1.01 is preferentially used. Available secondary data (country v.1.04、foreign country v.1.0) is used if the items don't correspond to basic data v.1.01.			

6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	—
6.3	Verification ID	CV-DG01-15014	6.4	Completion date of verification	2015/3/13

7	Remarks	Revised on April 1st, 2021: Implemented the company name change.
---	---------	--

(*) For secondary data, refer to the following page on the CFP website.
<http://www.cfp-japan.jp/calculate/verify/data.html>