Registration Information Carbon Footprint of Products (CFP)



1. Pro	duct information		
1.1	Registration number	CR-DG02-18018-A	1.7 Product photo
1.2	Registration name	Xerox VersaLink C9000 Printer (Desktop)	
1.3	Model name / number	Xerox VersaLink C9000 Printer (Desktop)	
1.4	Main specifications of product	Print speed (Color/Mono): 55ppm/55ppm (Letter) Maximum Paper size: SRA3(320.0×450.0mm) Capable of print, duplex printing. Product Size: 620.0(W)x723.0(D)x721.0(H) (mm) Product weight: 80.8kg	
1.5	CFP quantification unit	Per unit product	
1.6	CFP release date	October 31st, 2018	

2. Company Information				
2.1	Company name (in English)	FUJIFILM Business Innovation Corp.		
2.2	Phone number (incl. area code)	+81-3-6271-5111		

3. CFF	P quantification results, ar	nd description of CFP declration	
3.1	CFP quantification results	2,400	kg-CO2e
	Breakdown (by life cyc	le stage, by process, by flow, etc.)	
	Raw material acquisition stage	610	kg-CO ₂ e
3.2	Production stage	20	kg-CO ₂ e
3.2	Distribution stage	46	kg-CO ₂ e
	Use & maintenance stage	1,700	kg-CO ₂ e
	Disposal & recycling stage	32	kg-CO ₂ e
	Value in CFP mark and o	lescription of additional info.	
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>
	Value in CFP mark	2,400kg	per unit product
3.3		*Electric power in the use and ma power-consumption-rate in the U *Print volume is assumed 1,815,0 *In this scenario, the CO ₂ emissio 4.0g per A4 paper.	
	Description of additional info.	Disposal & recycling stage 1% Use & maintenance stage 73%	Raw material acquisition stage 23% Production stage 1% Distribution stage 2%
3.4	Remarks		

4. Interpretation of CFP quantification results				
4. Inter	Interpretation of CFP quantification results	 CO2 emission in use and maintenance stage is the largest as 73%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 470kg-CO2e of the CO2 emissions (approximately 18%) can be reduced if 2-in-1 print is applied to 907,500 sheets (50% of the estimated total print volume). Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above. 		

5. Conditions of quantification					
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
5.3	Assumptions of	Basic secondary data v.1 (country v.1.04、foreign c basic data v.1.01.			ailable secondary data items don't correspond to

6. Ver	6. Verification information					
6.1	Verification method	CFP system certification	6.2	CFP system certification No.	SCN16001	
6.3	Verification ID	FX-2018-003	6.4	Completion date of verification	October 26th, 2018	

7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	<u>http://www.cfp-japan.jp/</u>
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8 Remarks Revised on April 1st, 2021: Implemented the company name change.

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html