## Registration Information Carbon Footprint of Products (CFP)



1. Prod	roduct information		
1.1	Registration number	CR-DG02-20001	1.7 Product photo
1.2	Registration name	ApeosPort-VI C2271 PFS	1/4
1.3	Model name / number	ApeosPort-VI C2271 PFS	
1.4		Print speed (Color/Mono): 25ppm/25ppm (Letter) Maximum Paper size: SRA3(320.0×450.0mm) Capable of print/copy/scan/fax, duplex printing. Product Size: 669(W)x723(D)x1,141(H) (mm) Product weight: 132kg	
1.5	CFP quantification unit	Per unit product	
1.6	CFP release date	February 10th, 2020	<b>—</b>

2. Cor	npany Information	
2.1	Company name (in English)	Fuji Xerox Co., Ltd.
2.2	Phone number (incl. area code)	+81-3-6271-5111

3 CFF	Quantification results and	d description of CFP declration	
3.1	CFP quantification results	1,000	kg-CO2e
	Breakdown (by life cycl	e stage, by process, by flow, etc.)	
	Raw material acquisition stage	830	kg-CO₂e
3.2	Production stage	20	kg-CO₂e
3.2	Distribution stage	26	kg-CO₂e
	Use & maintenance stage	76	kg-CO₂e
	Disposal & recycling stage	49	kg-CO₂e
	Value in CFP mark and d	escription of additional info.	
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>
	Value in CFP mark	1,000kg	per unit product
3.3	Description of additional info.	*Electric power in the use and ma power-consumption-rate in Japan *Print volume is assumed 90,000 *In this scenario, the CO <sub>2</sub> emissio per A4 paper. *The CO <sub>2</sub> emission of printing pap	stage assumes Japan as the main sales area. intenance stage is evaluated with the public electrics. sheets. ns from copy papers are estimated 690 kg-CO <sub>2</sub> e at 4.0g per is excluded from the use and maintenance stage. sevaluated based on TEC value which is measured in RGY STAR Program version 3.0.
3.4	Remarks		

Interpretation of CFP quantification results		ation results
4. Inte	Interpretation of CFP	CO2 emission in use and maintenance stage is the largest as 83%. It is important to reduce size and weight.  The use condition in this scenario can be different from the use condition of the user.  A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage.  For example, 18kg-CO2e of the CO2 emissions (approximately 1.9%) can be reduced if 2-in-1 print is applied to 45,000 sheets (50% of the estimated total print volume).
		Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts.  Please understand this result as the rough estimate according to the reason mentioned above.

5. Cor	ditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
5.3	Assumptions of	Basic secondary data v.1. (domestic country v.1.04, to basic data v.1.01.		,	illable secondary data d if the items don't correspond

6. Veri	fication information				
6.1	Verification method	CFP system certification	6.2	CFP system certification No.	SCN16001
6.3	Verification ID	FX-2018-007	6.4	Completion date of verification	January 30th, 2020

7. Pro	gram information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Sustainable ManagementPromotion Organization(SuMPO)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks
---	---------

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html