## Registration Information Carbon Footprint of Products (CFP)



1. Prod	duct information		
1.1	Registration number	CR-DG02-20003	1.7 Product photo
1.2	Registration name	ApeosPort-VI C3371 PFS-2TS	
1.3	Model name / number	ApeosPort-VI C3371 PFS-2TS	
1.4	Main specifications of product	Print speed (Color/Mono): 35ppm/35ppm (Letter) Maximum Paper size: SRA3(320.0×450.0mm) Capable of print/copy/scan/fax, duplex printing. Product Size: 642(W)x723(D)x970(H) (mm) Product weight: 119kg	
1.5	CFP quantification unit	Per unit product	w e
1.6	CFP release date	February 10th, 2020	A - A

2	2. Con	npany Information	
	2.1	Company name (in English)	Fuji Xerox Co., Ltd.
	2.2	Phone number (incl. area code)	+81-3-6271-5111

	ar a la l		
3. CFF	. '	d description of CFP declration	
3.1	CFP quantification results	990	kg-CO2e
	Breakdown (by life cycle	e stage, by process, by flow, etc.)	
	Raw material acquisition stage	780	kg-CO₂e
3.2	Production stage	20	kg-CO <sub>2</sub> e
3.2	Distribution stage	24	kg-CO <sub>2</sub> e
	Use & maintenance stage	130	kg-CO <sub>2</sub> e
	Disposal & recycling stage	44	kg-CO <sub>2</sub> e
	Value in CFP mark and d	escription of additional info.	
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>
	Value in CFP mark	990kg	per unit product
3.3	Description of additional info.	*Electric power in the use and mai power-consumption-rate in Japan. *Print volume is assumed 182,400 *In this scenario, the CO <sub>2</sub> emission per A4 paper. *The CO <sub>2</sub> emission of printing pap	ation.  Intege assumes Japan as the main sales area.  Intenance stage is evaluated with the public electrical sheets.  In sheets.  In sheets are estimated 1,400 kg-CO <sub>2</sub> e at 4.0g  In sheets are estimated 1,400 kg-CO <sub>2</sub> e at 4.0g  In sheets are evaluated based on TEC value which is measured in
3.4	Remarks		
J. <del>T</del>	Remaiks		

	CO2 emission in use and maintenance stage is the largest as 78%. It is important to
erpretation of CFP antification results	reduce size and weight.  The use condition in this scenario can be different from the use condition of the user.  A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage.  For example, 32kg-CO2e of the CO2 emissions (approximately 3.2%) can be reduced if 2-in-1 print is applied to 91,200 sheets (50% of the estimated total print volume).  Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts.
	rpretation of CFP ntification results

5. Cor	nditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
5.3	Assumptions of	Basic secondary data v.1. (domestic country v.1.04, to basic data v.1.01.		,	illable secondary data d if the items don't correspond

I	6. Veri	fication information				
	6.1	Verification method	CFP system certification	6.2	CFP system certification No.	SCN16001
ĺ	6.3	Verification ID	FX-2019-003	6.4	Completion date of verification	January 30th, 2020

7. Pro	gram information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Sustainable ManagementPromotion Organization(SuMPO)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks
---	---------

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html