## Registration Information Carbon Footprint of Products (CFP)



1. Pro	duct information		
1.1	Registration number	CR-DG02-20005	1.7 Product photo
1.2	Registration name	DocuCentre-VI C5571 PFS	
1.3	Model name / number	DocuCentre-VI C5571 PFS	
1.4	Main specifications of product	Print speed (Color/Mono): 55ppm/55ppm (Letter) Maximum Paper size: SRA3(320.0×450.0mm) Capable of print/copy/scan/fax, duplex printing. Product Size: 669(W)x723(D)x1,141(H) (mm) Product weight: 132kg	
1.5	CFP quantification unit	Per unit product	
1.6	CFP release date	February 10th, 2020	

2. Cor	npany Information	
2.1	Company name (in English)	Fuji Xerox Co., Ltd.
2.2	Phone number (incl. area code)	+81-3-6271-5111

2 CEL	augntification regults on	d description of CFP declration	
3. UFF	•	ı	T
3.1	CFP quantification results	1,200	kg-CO2e
	Breakdown (by life cycl	e stage, by process, by flow, etc.)	
	Raw material acquisition stage	830	kg-CO₂e
3.2	Production stage	20	kg-CO <sub>2</sub> e
3.2	Distribution stage	26	kg-CO <sub>2</sub> e
	Use & maintenance stage	310	kg-CO <sub>2</sub> e
	Disposal & recycling stage	50	kg-CO <sub>2</sub> e
	Value in CFP mark and d	escription of additional info.	
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>
	Value in CFP mark	1,200kg	per unit product
3.3	Description of additional info.	*Electric power in the use and mai power-consumption-rate in Japan. *Print volume is assumed 451,200 *In this scenario, the CO <sub>2</sub> emission per A4 paper. *The CO <sub>2</sub> emission of printing pap	etage assumes Japan as the main sales area. intenance stage is evaluated with the public electric- b. in sheets. In strom copy papers are estimated 3,500 kg-CO <sub>2</sub> e at 4.0g over is excluded from the use and maintenance stage. In evaluated based on TEC value which is measured in
3.4	Remarks		
ــــــــــــــــــــــــــــــــــــــ			

4. Inte	pretation of CFP quantific	ation results
4. Inte	Interpretation of CFP	CO2 emission in use and maintenance stage is the largest as 67%. It is important to reduce size and weight.  The use condition in this scenario can be different from the use condition of the user.  A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage.  For example, 76kg-CO2e of the CO2 emissions (approximately 6.2%) can be reduced if 2-in-1 print is applied to 225,600 sheets (50% of the estimated total print volume).  Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts.  Please understand this result as the rough estimate according to the reason
		Please understand this result as the rough estimate according to the reason mentioned above.

Ļ	5. Con	ditions of quantification				
Ī	5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
	5.3	Assumptions of	Basic secondary data v.1. (domestic country v.1.04, to basic data v.1.01.		,	allable secondary data d if the items don't correspond

6. Ve	ification information				
6.1	Verification method	CFP system certification	6.2	CFP system certification No.	SCN16001
6.3	Verification ID	FX-2019-001	6.4	Completion date of verification	January 24th, 2020

7. Pro	gram information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Sustainable ManagementPromotion Organization(SuMPO)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks
---	---------

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html