## Registration Information Carbon Footprint of Products (CFP)



1. Pro	duct information		
1.1	Registration number	CR-DG02-20007	1.7 Product photo
1.2	Registration name	DocuCentre-VI C6671 PFS	
1.3	Model name / number	DocuCentre-VI C6671 PFS	
1.4	Main specifications of product	Print speed: Color 65ppm/Monochrome 65ppm Maximum Paper size: SRA3(320x450mm) Capable of print/copy/scan/FAX, duplex printing. Product Size: 620(W)x793(D)x1,169(H) (mm) Product weight: 155kg	
1.5	CFP quantification unit	Per unit product	am
1.6	CFP release date	March 18th, 2020	

2. Cor	2. Company Information		
2.1	Company name (in English)	Fuji Xerox Co., Ltd.	
2.2	Phone number (incl. area code)	+81-3-6271-5111	

3. CFF	P quantification results, and	d description of CFP declration		
3.1	CFP quantification results	1,600 kg-CO2e		
	Breakdown (by life cycl	e stage, by process, by flow, etc.)		
	Raw material acquisition stage	950	kg-CO <sub>2</sub> e	
3.2	Production stage	19	kg-CO <sub>2</sub> e	
3.2	Distribution stage	31	kg-CO <sub>2</sub> e	
	Use & maintenance stage	500	kg-CO <sub>2</sub> e	
	Disposal & recycling stage	55	kg-CO <sub>2</sub> e	
	Value in CFP mark and de	escription of additional info.		
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>	
	Value in CFP mark	1,600kg	per unit product	
3.3	Description of additional info.	*Calculated on the basic configu *CO <sub>2</sub> emission in the distribution *Electric power in the use and r power-consumption-rate in Japa *Print volume is assumed 630,0 *In this scenario, the CO <sub>2</sub> emission 4.0g per A4 paper. *The CO <sub>2</sub> emission of printing p *Electric power in the use stage	n stage assumes Japan as the main sales area. maintenance stage is evaluated with the public electric- an. 000 sheets based on ENERGY STAR Program ver. 3.0. sions from copy papers are estimated 4,900 kg-CO <sub>2</sub> e at eaper is excluded from the use and maintenance stage. Is evaluated based on TEC value which is measured in NERGY STAR Program version 3.0. Raw material acquisition stage 61%	
3.4	Remarks			
J.4	I CILIAI NS			

4. Inter	4. Interpretation of CFP quantification results			
4.1	Interpretation of CEP	CO2 emission in use and maintenance stage is the largest as 61%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 125kg-CO2e of the CO2 emissions (approximately 8%) can be reduced if 2-in-1 print is applied to 50% of the estimated total print volume. Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.		

5. Cor	5. Conditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
5.3	Assumptions of	Basic secondary data v.1.01 is preferertially used. Available secondary data domestic country v.1.04, foreign country v.1.0) is used if the items don't correspond to basic data v.1.01.			

ĺ	6. Veri	fication information				
	6.1	Verification method	CFP system certification	6.2	CFP system certification No.	SCN16001
ĺ	6.3	Verification ID	FX-2019-005	6.4	Completion date of verification	March 10th, 2020

7. Pro	7. Program information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	<u>http://www.cfp-japan.jp/</u>
7.3	Program operator	Sustainable ManagementPromotion Organization(SuMPO)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

	8	Remarks	-
--	---	---------	---

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html