## Registration Information Carbon Footprint of Products (CFP)



1. Prod	duct information		
1.1	Registration number	CR-DG02-20013	1.7 Product photo
1.2	Registration name	Xerox PrimeLink B9125 Copier/Printer	
1.3	Model name / number	Xerox PrimeLink B9125 Copier/Printer	
1.4	Main specifications of product	Print speed (Mono): 125ppm (Letter) Maximum Paper size: 330mmx488mm Capable of print/copy/scan, duplex printing. Product Size: 2,339(W)x913(D)x1,477(H) (mm) Product weight: 392kg	
1.5	CFP quantification unit	Per unit product	
1.6	CFP release date	February 17th, 2020	

2. Cor	npany Information	
2.1	Company name (in English)	Fuji Xerox Co., Ltd.
2.2	Phone number (incl. area code)	+81-3-6271-5111

3. CFF	guantification results, and	d description of CFP declration	
3.1	CFP quantification results	13,000	kg-CO2e
	Breakdown (by life cycle	e stage, by process, by flow, etc.)	
	Raw material acquisition stage	1,900	kg-CO <sub>2</sub> e
3.2	Production stage	18	kg-CO₂e
3.2	Distribution stage	430	kg-CO₂e
	Use & maintenance stage	10,000	kg-CO₂e
	Disposal & recycling stage	120	kg-CO <sub>2</sub> e
	Value in CFP mark and de	escription of additional info.	
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>
	Value in CFP mark	13,000kg	per unit product
3.3	Description of additional info.	area.  *Electric power in the use and r power-consumption-rate in the *Print volume is assumed 9,370 *In this scenario, the CO <sub>2</sub> emiss 4.0g per A4 paper.  *The CO <sub>2</sub> emission of printing p *Electric power in the use stage	uration. In stage assumes the United States as the main sales maintenance stage is evaluated with the public electric- United States. D,000 sheets. Sions from copy papers are estimated 72,000 kg-CO <sub>2</sub> e at paper is excluded from the use and maintenance stage. The experimental ex
		Disposal & recycling stage 1% Use & maintenance stage 80%	Raw material acquisition stage 15%  Production stage 0.2%  Distribution stage 4%
3.4	Remarks		

4. Inte	rpretation of CFP quantific	cation results
4.11	Interpretation of CED	CO2 emission in use and maintenance stage is the largest as 80%. It is important to save energy during product usage.  The use condition in this scenario can be different from the use condition of the user.  A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage.  For example, 2,500kg-CO2e of the CO2 emissions (approximately 20%) can be reduced if 2-in-1 print is applied to 50% of the estimated total print volume.  Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.

5. Cc	nditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
5.3	Assumptions of	Basic secondary data v.1 (domestic country v.1.04, correspond to basic data	forei	gn country v.1.0) is use	

6. Veri	fication information				
6.1	Verification method	CFP system certification	6.2	CFP system certification No.	SCN16001
6.3	Verification ID	FX-2020-003	6.4	Completion date of verification	February 7th, 2020

7. Pro	gram information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Sustainable ManagementPromotion Organization(SuMPO)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8 Remarks
-----------

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html