Registration Information Carbon Footprint of Products (CFP)



1. Product information				
1.1	Registration number	CR-DG02-19034	1.7 Product photo	
1.2	Registration name	Xerox PrimeLink C9065 Printer		
1.3	Model name / number	Xerox PrimeLink C9065 Printer	a	
1.4	Main specifications of product	Print speed (Color/Mono): 65ppm/70ppm (Letter) Maximum Paper size: SRA3(320.0×450.0mm) Capable of print, duplex printing. Product Size: 1574.0(W)x804.0(D)x1392.0(H) (mm) Product weight: 237kg		
1.5	CFP quantification unit	Per unit product		
1.6	CFP release date	October 1st, 2019		

2. Company Information			
2.1	Company name (in English)	Fuji Xerox Co., Ltd.	
2.2	Phone number (incl. area code)	+81-3-6271-5111	

3.1 CFP quantification results Breakdown (by life cycle stage, by process, by flow, etc.) Raw material acquisition stage Production stage 22 kg-CO ₂ e Use & maintenance stage Disposal & recycling stage Value in CFP mark and description of additional info. Numerial value> Calculated by the standard Scenario for MFP (EP type). Calculated on the basic configuration. *CO ₂ emission in the distribution stage assumes the United States as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 2,940,000 sheets. 1n this scenario, the CO ₂ emissions from copy papers are estimated 23,000 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. *Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0. Disposal & recycling stage *In this scenario, the CO ₂ emissions from copy papers are estimated 23,000 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. *Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0. Disposal & recycling stage 110	2 055	OFD world of the county of the			
Breakdown (by life cycle stage, by process, by flow, etc.) Raw material acquisition stage Production stage 22 kg-CO ₂ e Distribution stage Disposal & recycling stage Value in CFP mark Calculated by the standard Scenario for MFP (EP type). Calculated by the standard Scenario for MFP (EP type). Calculated on the basic configuration. *CO ₂ emission in the distribution stage assumes the United States as the main sales area. Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 2,940,000 sheets. In this scenario, the CO ₂ emissions from copy papers are estimated 23,000 kg-CO ₂ e at 4.0g per A4 paper. The CO ₂ emission of printing paper is excluded from the use and maintenance stage. Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0. Disposal & recycling stage Use & maintenance stage Production stage 0.3% Distribution stage Distribution stage Distribution stage Distribution stage	3. CFF	P quantification results, and description of CFP decIration			
Raw material acquisition stage Production stage Distribution stage Disposal & recycling stage Disposal & recycling stage Value in CFP mark and description of additional info. *Calculated by the standard Scenario for MFP (EP type). *Calculated on the basic configuration. *CO2 emission in the distribution stage assumes the United States as the main sales area. *Flectric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 2,940,000 sheets. *In this scenario, the CO2 emissions from copy papers are estimated 23,000 kg-CO2e at 4.0g per A4 paper. *The CO2 emission of printing paper is excluded from the use and maintenance stage. *Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0. Disposal & recycling stage *Raw material acquisition stage 21% Production stage 0.3% Use & maintenance stage Take *Distribution stage Distribution stage Distribution stage Distribution stage Distribution stage	3.1	results	· ·	kg-CO2e	
Stage		Breakdown (by life cycle stage, by process, by flow, etc.)			
Distribution stage Disposal & recycling stage Calculated by the standard Scenario for MFP (EP type). Calculated by the standard Scenario for MFP (EP type). Calculated on the basic configuration. *CO ₂ emission in the distribution stage assumes the United States as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 2,940,000 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 23,000 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. *Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0. Disposal & recycling stage Distribution stage 2% Distribution stage 2% Distribution stage 4% Distribution stage 4%		•	1,400	kg-CO ₂ e	
Distribution stage Use & maintenance stage Disposal & recycling stage 110 kg-CO ₂ e Value in CFP mark and description of additional info. Value in CFP mark 6,800kg Per unit product *Calculated by the standard Scenario for MFP (EP type). *Calculated on the basic configuration. *CO ₂ emission in the distribution stage assumes the United States as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 2,940,000 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 23,000 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. *Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0. Disposal & recycling stage Production stage 2% Raw material acquisition stage 21% Distribution stage 4% Distribution stage	2.0	Production stage	22	kg-CO ₂ e	
Disposal & recycling stage Value in CFP mark and description of additional info. *CNumerial value>	3.2	Distribution stage	250	kg-CO ₂ e	
Value in CFP mark and description of additional info. Value in CFP mark Characteristic		Use & maintenance stage	5,000	kg-CO ₂ e	
Value in CFP mark 6,800kg per unit product *Calculated by the standard Scenario for MFP (EP type). *Calculated on the basic configuration. *CO ₂ emission in the distribution stage assumes the United States as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 2,940,000 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 23,000 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. *Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0. Disposal & recycling stage 21% Production stage 0.3% Distribution stage 4%		Disposal & recycling stage	110	kg-CO₂e	
*Calculated by the standard Scenario for MFP (EP type). *Calculated on the basic configuration. *CO ₂ emission in the distribution stage assumes the United States as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 2,940,000 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 23,000 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. *Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0. Disposal & recycling stage 21% Production stage 0.3% Distribution stage 4%		Value in CFP mark and o	•		
*Calculated by the standard Scenario for MFP (EP type). *Calculated on the basic configuration. *CO ₂ emission in the distribution stage assumes the United States as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 2,940,000 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 23,000 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. *Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0. Disposal & recycling stage 21% Production stage 0.3% Distribution stage 4%			<numerial value=""></numerial>	<unit for="" the="" value=""></unit>	
*Calculated on the basic configuration. *CO ₂ emission in the distribution stage assumes the United States as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 2,940,000 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 23,000 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. *Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0. Disposal & recycling stage 21% Production stage 21% Use & maintenance stage 74% Distribution stage 4%		Value in CFP mark	6,800kg	per unit product	
	3.3		*Calculated on the basic configur *CO ₂ emission in the distribution area. *Electric power in the use and ma power-consumption-rate in the U *Print volume is assumed 2,940,0 *In this scenario, the CO ₂ emission 4.0g per A4 paper. *The CO ₂ emission of printing pa *Electric power in the use stage is acordance with International ENE Disposal & recycling stage 2% Use & maintenance stage	ration. stage assumes the United States as the main sales aintenance stage is evaluated with the public electric- nited States. 2000 sheets. ons from copy papers are estimated 23,000 kg-CO ₂ e at per is excluded from the use and maintenance stage. Is evaluated based on TEC value which is measured in ERGY STAR Program version 3.0. Raw material acquisition stage 21% Production stage 0.3% Distribution stage	
3.4 Remarks	3.4	Remarks			

4. Interpretation of CFP quantification results					
		CO2 emission in use and maintenance stage is the largest as 74%. It is important to save energy during product usage.			
4.1	Interpretation of CFP quantification results	The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 1,200kg-CO2e of the CO2 emissions (approximately 18%) can be reduced if 2-in-1 print is applied to 1,470,000 sheets (50% of the estimated total print volume). Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.			

5. Cor	5. Conditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
5.3	Assumptions of	Basic secondary data v.1.01 is preferertially used. Available secondary data (domestic country v.1.04, foreign country v.1.0) is used if the items don't correspond to basic data v.1.01.			

I	6. Verification information					
	6.1	Verification method	CFP system certification	6.2	CFP system certification No.	SCN16001
ĺ	6.3	Verification ID	FX-2019-006	6.4	Completion date of verification	September 26th, 2019

7. Pro	7. Program information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

ı	8	Remarks	-

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html