Registration information of Carbon Footprint of Products

1. Pro	duct information		
1.1	Registration number	CR-DG01-13008	1.7 Product photo
1.2	Product name	Xerox Phaser 7100 Color Printer	
1.3	Product model	Xerox Phaser 7100	
1.4	Main specifications of product	Print speed (Letter/A4): 30ppm color/black-and-white Paper size: A3 maximum Capable of duplex printing Product Size: 499.5(W)x538(D)x406(H) (mm) Product weight: 45kg (Xerox Phaser 7100DN model)	
1.5	CFP quantification unit	Per unit product	
1.6	Date of release	2013/10/3	

2. Con	npany Information	
2.1	Company name	Fuji Xerox Co., Ltd.
2.2	Phone number	+81-3-6271-5111

3. CFF	o quantification results, ar	d contents of CFP decIration	
3.1	CFP quantification results	2,000	kg-CO ₂ e (CFP quantification results can be slightly different from sum of thefollowing breakdown for rounding of fractions.)
	Breakdown (by life cyc	e stage, by process, by flow, etc.)	
	Raw material acquisition stage	270	kg-CO₂e
3.2	Production stage	43	kg-CO₂e
3.2	Distribution stage	46	kg-CO₂e
	Use & maintenance stage	1,600	kg-CO₂e
	Disposal & recycling stage	70	kg-CO₂e
	Value in a mark, and co	ntents of additional info.	
		<contents></contents>	<unit a="" for="" in="" mark="" the="" value=""></unit>
	Value in a mark	2,000kg	per unit product
3.3	Contents of additional info.	electric-power-consumption-ra *The CO2 value is evaluated of function. The difference from r	Distribution stage Use & maintenance stage Disposal & recycling stage maintenance stage is evaluated with the public
3.4	Remarks	*Print volume: $540,000$ sheets *In this scenario, the CO_2 emis CO_2 e at 4.0 g per A4 paper.	sions from copy papers are estimated 4,200 kg-

4. Inte	erpretation of CFP quantifi	cation results
4.1	Interpretation of CFP	CO ₂ emission in use and maintenance stage is the largest as 79%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO ₂ emission during product usage. For example, 290kg-CO ₂ e of the CO ₂ emissions (approximately 14%) can be reduced if 2-in-1 print is applied to 270,000sheets (50% of print volume). CO ₂ emission in raw material acquisition stage is the second largest as 14%. It is also important to reduce size and weight. Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.

5. Con	ditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
5.3		Basic secondary data v.1.0° v.1.03, foreign country v.1.0			e secondary data (country rrespond to basic data v.1.01.

6. Veri	ification information				
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	
6.3	Verification ID	CV-DG01-13008	6.4	Completion date of verification 2013/9/24	

7 Remarks —

^(*) For secondary data, refer to the following page on the CFP website. http://www.cfp-japan.jp/calculate/verify/data.html