Registration information of Carbon Footprint of Products

1. Product information					
1.1	Registration number	CR-DG01-12009-1	1.7 Product photo		
1.2	Product name	Color Multifunction Office Systems			
1.3	Product model	imageRUNNER ADVANCE C9270 PRO	- Michael		
1.4	Main specifications of product	Print speed (BW/CL): 70/60 ppm (A4) Paper size: A3 maximum Standardized automatic duplexing Functionality 1,180mm(W)×932mm(D)×1,403mm(H) Product weight: Approximately 279kg	0- 1-0		
1.5	CFP quantification unit	Per unit product	14.0		
1.6	Date of release	12/04/2012			

2. Company Information				
2.1	Company name	Canon Inc.		
2.2	Phone number	+81-3-3758-2111		

3. CFF	o quantification results, and	d contents of CFP declration					
3.1	CFP quantification results	6100	kg-CO ₂ e (CFP quantification re following breakdown f	0 ,	different from sum of the		
	Breakdown (by life cycle stage, by process, by flow, etc.)						
	Raw material acquisition stage	1700	kg-CO₂e				
	Production stage	190	kg-CO₂e				
3.2	Distribution stage	83	kg-CO₂e				
	Use & maintenance stage	4000	kg-CO ₂ e				
	Disposal & recycling stage	200	kg-CO ₂ e				
	Value in a mark, and co	ntents of additional info.					
		<contents></contents>	<unit a="" for="" in="" mark<="" td="" the="" value=""><td>a mark></td></unit>		a mark>		
	Value in a mark 6,100kg		Per unit product				
3.3	Contents of additional info.	 ●The CO₂ emissions from the copy papers are excluded in 3.1. ●Scenario: Multifunction Device (EP type) ●Sales area: around the world. ●CO₂ emission of Distribution stage is quantified by the shipping ratio. ●Print volume: 2,918,000 sheets. ●In this scenario, the CO₂ emissions from copy papers are estimated 27,000kg-CO₂e at 4.0g per A4 paper. ●1,100kg-CO₂e of the CO₂ emissions (approximately 17%) can be reduced if 2-in-1 print is applied to 1,459,000 sheets (50%of print volume). 6,700kg-CO₂ of the CO₂ emissions from the copy papers can also be reduced. 		Disposal & recycling stage 3% Use & maintena nce stage 65%	Raw material acquisitio n stage 28% Productio n stage 3% Distributi on stage 1%		
3.4	Remarks	CFP quantification results[kg-CO ₂ e]=1.40 E-03×print volume[sheets]+2.01 E+03 (more than 50,000 sheets)					

4. Interpretation of CFP quantification results					
4.1	Interpretation of CFP	CO2 emission in Use & maintenance stage is the largest as 65%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 1,100kg-CO2e of the CO2 emissions (approximately 17%) can be reduced if 2-in-1 print is applied to 1,459,000 sheets (50%of print volume). CO2 emission in Raw material acquisition stage is the second largest as 28%. It is also important to reduce size and weight. Primary data is used in the raw material consumption. Secondaty data is used in the parts manufactureing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as a rough estimate according to the reason mentioned above.			

5. Con	5. Conditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
5.3		Basic secondary data v.1 v.1.01 is used if the items			

6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	-
6.3	Verification ID	CV-DG01-12009	6.4	Valid period of verification	11/11/2015

		04/04/0040 D 11 11 11 11 11 11 11 11 11 11 11 11 1
7	Remarks	01/24/2013 Registration information 3. and 4. are modified.

^(*) For secondary data, refer to the following page on the CFP website. http://www.cfp-japan.jp/calculate/verify/data.html